

Etron

鈺創科技

Etron Technology, Inc.

PRELIMINARY DATA SHEET

EJ188

USB 3.0 Host Controller

Publication Version:

0.9

Publication Date:

2011/09/1

Approval:

To:

Etron Technology, Inc.

Add: No.6, Technology Road 5, Hsinchu Science Park, Hsinchu City, 30078, Taiwan, R.O.C.

P.O. Box: 19-54

Tel: 886-3-5782345

Fax: 886-3-5633037

<http://www.etrон.com>

©2011 Etron Technology, Inc.

This document may be modified or revised subject to the discretion of Etron Technology, Inc. without further notice. Etron Technology, Inc. makes no warranty or representation to either the contents of this document or the products referenced in this document for any errors or omissions.

Table of Contents



1. Introduction

The EJ188 is a PCIe Gen 2 to Universal Serial Bus 3.0 host controller, which complies with PCIe Rev 2.0 specification, USB3.0 specification and eXtensible Host Controller Interface (xHCI) 1.0.

The EJ188 has a PCIe Gen2 x1 lanes for the PC host system and four USB3.0 downstream ports, which provide SuperSpeed, HighSpeed, FullSpeed and LowSpeed signals for USB 3.0 compliant peripherals and existing USB 2.0/1.1 peripheral devices.




Figure 1: EJ188 Block Diagram

2. Features

◆ Host Interface

- Compliant with the PCI Express Base Specification Revision 2.0
 - Support PCIe Gen2 x1 lanes
- Supports the PCI Bus Power Management Interface Specification Revision 1.2
- Supports the SPI/I2C type ROM/flash
- System clock uses either 25MHz crystal or external clock
- 3.3V for I/O power and 1.2V for core power

◆ USB interface

- Compliant with the Universal Serial Bus 3.0 specification Revision 1.0
 - Supports data rate :
 - LowSpeed(1.5 Mbps)
 - FullSpeed(12 Mbps)
 - HighSpeed(480 Mbps)
 - SuperSpeed(5 Gbps)
 - Four downstream USB3.0 ports
 - Support USB data transfer types:
 - Control
 - Bulk(stream)
 - Interrupt
 - Isochronous transfer
 - Compliant with eXtensible Host Controller Interface (xHCI) Specification revision 1.0

◆ Package

- 88-QFN (10 x 10)